



# Producer Statement and Maintenance Guide

# Promax

LIQUID MANAGEMENT SOLUTIONS



AS/NZS 4766 BMP No 657394  
Australian/New Zealand Standards

**Date:** 01.04.2018

**Product Code:** XPBT03500

**Product Description:** Promax Xpress Water Tank - 3,500 litres

**Product Specifications:** 1850mm Dia x 1640mm High with 450mm ID Manhole Riser and Vented Lid 25mm BSP threaded Base Outlet, Weight 70kg  
Complies with AS/NZS 4020, AS/NZS 2070 and AS/NZS 4766 (INT) Potable Water Standards and Chemical Storage.

**Product Uses:** Potable Water Storage  
Retention/Detention Stormwater Management  
Waste Storage

**Producer Statement:** In line with today's focus on Ecologically Sustained Development, Green Building Initiatives and 5 Star Ratings, Promax is committed to supplying quality Liquid Storage and Handling Solutions

Promax plastics manufactures these tanks to a high standard of quality. This Promax Tank may be used for retention/detention and/or the storage of potable water, storm water and waste water with the appropriate NZ Standards.

Promax Plastics confirms that if these tanks are installed according to Good Management practices set out in the Promax Installation Guide, they will perform as stated throughout their intended life.

Maintenance Guide:	Description	Action	Frequency
	Tank Stability	Tank must remain level, foundation must not become eroded or the tank lift	Monthly
	Tank Lid	Remains securely fitted	Bi-monthly
	Inlet/Outlet Fitting	Remains securely fitted with no leakage	Bi-monthly
	Pump	Check Pump, if fitted, for inlet screen blockages	Bi-monthly
	Sediment Build Up	Remains lower than base outlet - if outlet flow becomes restricted remove sediment with vacuum truck. Re-attach tank lid securely.	Half yearly or as necessary

**Please note: Entry into this tank is at owners risk.**

**Authorised By:** Promax Engineered Plastics Limited  
PO Box 749, Kerikeri 0245,  
New Zealand