

# Product Specification and Maintenance Guide

## PSMG-PMXUT03000ST

**Date** September 2021

**Code** PMXUT03000ST

**Description** Promax Septic Tank 3000L

### Specifications

Capacity (L)	Diameter (mm)	Length (mm)	Manhole Dia (mm)	Outlets (mm)
3000	1280	3100	600	1x 100mm

**Standard** Complies with:

- AS/NZS:1546 Standard for Septic Tanks

**Uses**

- Primary Treatment of Septic Waste

**Statement** In line with today's focus on Ecologically Sustained Development, Green Building Initiatives and 5 Star Ratings, Promax is committed to supplying quality Liquid Storage and Handling Solutions

Promax Plastics confirms that if these tanks are installed according to Good Management practices set out in the Promax Installation Guides, they will perform as stated throughout their intended life.

### Maintenance

Description	Action	Frequency
Tank Lid	Remains securely fitted	Bi-Monthly
Inlet/Outlet Fitting	Remains securely fitted with no leakage	Bi-Monthly
Pump	Check Pump, if fitted, for inlet screen blockages	Bi-Monthly
Sludge Build Up	Remove sludge with vacuum truck. Re-attach tank lid securely.	Minimum 3 years or as necessary

**Please note: Entry into this tank is at owners risk.**

### Authorised By:

Promax Engineered Plastics Limited  
PO Box 749, Kerikeri 0245, New Zealand



