

Product Specification and Maintenance Guide

PSMG-PMXSL05000

Date	July 2021
Code	PMXSL05000
Description	Promax Slimline Water Tank - 5000L

Specifications

Length (mm)	Width (mm)	Height (mm)	Weight (kg)	Manhole Dia (mm)
3000	910	2150	260	350

Standard	Includes 1x 25mm outlets Complies with: <ul style="list-style-type: none">AS/NZS 4020: Products in contact with drinking water.AS/NZS 2070: Plastics material for food contact use.
-----------------	---

Uses	<ul style="list-style-type: none">Water StorageRetention/Detention Stormwater Management
-------------	---

Statement	<p>In line with today's focus on Ecologically Sustained Development, Green Building Initiatives and 5 Star Ratings, Promax is committed to supplying quality Liquid Storage and Handling Solutions</p> <p>Promax Plastics confirms that if these tanks are installed according to Good Management practices set out in the Promax Installation Guides, they will perform as stated throughout their intended life.</p>
------------------	--

Maintenance

Description	Action	Frequency
Tank Stability	Tank must remain level, foundation must not become eroded	Monthly
Tank Lid	Remains securely fitted	Bi-Monthly
Inlet/Outlet Fitting	Remains securely fitted with no leakage	Bi-Monthly
Pump	Check Pump, if fitted, for inlet screen blockages	Bi-Monthly
Sediment Build Up	Remains lower than base outlet - if outlet flow becomes restricted remove sediment with vacuum truck. Re-attach tank lid securely.	Half yearly or as necessary

Please note: Entry into this tank is at owners risk.

Authorised By:

Promax Engineered Plastics Limited
PO Box 749, Kerikeri 0245, New Zealand



