

# Product Specification and Maintenance Guide

## PSMG-PMXSL02000PK

<b>Date</b>	July 2021
<b>Code</b>	PMXSL02000PK
<b>Description</b>	Promax Slimline Water Tank & Pump Combo - 2000L

### Specifications

Length (mm)	Width (mm)	Height (mm)	Weight (kg)	Manhole Dia (mm)
2250	570	2150	160	350

<b>Standard</b>	Includes 1x 25mm outlets Complies with: <ul style="list-style-type: none"><li>AS/NZS 4020: Products in contact with drinking water.</li><li>AS/NZS 2070: Plastics material for food contact use.</li></ul>
-----------------	---

<b>Uses</b>	<ul style="list-style-type: none"><li>Water Storage</li><li>Retention/Detention Stormwater Management</li></ul>
-------------	---

<b>Statement</b>	<p>In line with today's focus on Ecologically Sustained Development, Green Building Initiatives and 5 Star Ratings, Promax is committed to supplying quality Liquid Storage and Handling Solutions</p> <p>Promax Plastics confirms that if these tanks are installed according to Good Management practices set out in the Promax Installation Guides, they will perform as stated throughout their intended life.</p>
------------------	--

### Maintenance

Description	Action	Frequency
Tank Stability	Tank must remain level, foundation must not become eroded	Monthly
Tank Lid	Remains securely fitted	Bi-Monthly
Inlet/Outlet Fitting	Remains securely fitted with no leakage	Bi-Monthly
Pump	Check Pump, if fitted, for inlet screen blockages	Bi-Monthly
Sediment Build Up	Remains lower than base outlet – if outlet flow becomes restricted remove sediment with vacuum truck. Re-attach tank lid securely.	Half yearly or as necessary

**Please note: Entry into this tank is at owners risk.**

### Authorised By:

Promax Engineered Plastics Limited  
PO Box 749, Kerikeri 0245, New Zealand



